

Touch-Sensitive HD IP Conference Phone

Yealink CP965 is designed for medium and large-sized conference rooms. Based on Android 9.0 system, it is a flagship HD conference phone with powerful voice conferencing features and easy control operation. CP965 adopts a business and introverted design that perfectly matches the calm style of the conference room, but also a acoustic fabric, which is impervious to any accidental liquid spills. Its fingerprint-proof LCD screen with a clear UI interaction page makes it easy for everyone to control the meeting. CP965 has 13 built-in microphones, providing you with a clear and natural conference call experience. In addition, you can also connect CP965 to your mobile device (such as PC device, smart phone, etc.) via Bluetooth or USB to achieve a variety of UC hybrid meeting modes. CP965 can be connected with 3 CPs in star shape to realize synchronous sound pickup and playback, providing users with an optimum audio experience. CP965 provides you with a new intelligent voice conferencing solution, which is the ideal office assistant for your conference room.



Android 9



Yealink Decagon Meeting Room



Hybrid UC Meeting



Pairing via Bluetooth



Key Features and Benefits

Modest Design, Easy-to-Use User Interface

Yealink CP965 is a hermit in the conference room. Its black acoustics fabric can realize crystal-clear audio and is resistant to water, oil, and stain. Its ultra-thin body, appropriate desktop fit, and ingenious hidden wiring slot, perfectly fit for the simple business style in the conference rooms. Additionally, its built-in Android 9.0 system and easy-to-use UI interface, allow users to launch a meeting with one button and increase user adoption

HD Audio, Smooth Communication

CP965 adopts Y-shaped design and has 12 built-in microphones for sound picking and 1 microphone for noise cancellation. Its 20-foot and 360° omni-direction voice pickup provides users with clear and natural voice conference experience.

Rich Features and High Expandability

CP965 supports 10-way conference call, enabling participants from different locations to communicate smoothly, reducing costs for your company. You can also connect CP965 to your mobile devices (such as computer, smart phone, PSTN device CPN10, etc.) through Bluetooth or Type C or USB 2.0 port to realize Hybrid UC meeting (including PSTN, SIP, mobile phone). Moreover, when working with the DECT wireless expansion microphone CPW65, a up to 30-meter connection distance with CP965 can be achieved while still keeping the conference room table clean.

- Red Dot[2021]
- Android 9.0
- 5-inch multi-touch screen with 720x1280 resolution
- Optimal HD audio, full duplex technology
- Yealink Noise Proof Technology
- 20-foot (6-meter) and 360-degree voice pickup
- Built-in 12-microphone array for voice pickup
- Built-in 1-microphone array for noise cancellation
- Power over Ethernet
- 10-way conference call
- Hybrid UC meeting
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)

Audio Features

- Optimal HD audio
- Yealink Noise Proof Technology
- Smart Noise Filtering
- 13ft (4m) high-quality voice pickup range
Maximum 20ft (6m) voice pickup range
- Apply to medium to large conference room
- Built-in 12-microphone array, 360-degree voice pickup
- Built-in 1-microphone array, decrease noise
- Loudspeaker
 - Frequency: 100-20,000 Hz
 - Volume: 94 dB at 0.5-m peak volume
- 56mm diameter and 5w speaker
- Full-duplex speakerphone with AEC
- Echo cancellation tail length is up to 320ms
- Background noise suppression
- Codecs: G722, G722.1C, G726, G.729, G.729A, G723, iLBC, Opus, PCMU (G.711A), PCMA (G.711μ)
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- VAD, CNG, PLC, AJB, AGC

Phone features

- 1 SIP account
- Call hold, mute, DND, call recording, hotline
- 10-way conference call
- Analog PSTN calls via CPN10
- Redial, call waiting, emergency call
- Call forward, call transfer, call return, dial plan
- Ring tone selection/import/delete
- Set date time manually or automatically
- Volume adjustment
- Pairing via Bluetooth
- Create meeting directly
- Join meeting seamlessly
- Active Speaker

Star connection

- Up to four CP965: One Master CP, three Slave CP
- Wired network only
- Two expansion microphones for each CP965

Directory

- Local phonebook up to 1000 entries

- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Block list

IP-PBX features

- Busy Lamp Field (BLF)
- Multicast paging
- Intercom
- Anonymous call
- Anonymous call rejection
- Voice mail
- Distinctive ringtone
- Call pickup

Display

- 5" 720x1280 capacitive touch screen
- Volume key
- Home button

Interface

- 1 x RJ45 10/100M Ethernet port
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)
- Built-in Bluetooth 4.2
- Power over Ethernet (IEEE 802.3at), class 4
- 1 x USB 2.0 Type-A device port
- 1 x USB 2.0 Type-C device port
- 1 x Security slot

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server redundancy supported
- IPv4/IPv6
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice encryption
- Transport Layer Security (TLS1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)

- Adb encryption authenticated
- Digest authentication using MD5/SHA1/SHA224/SHA256/SHA384/SHA512
- OpenVPN, L2TP VPN
- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)

Management

- Configuration: browser/phone/auto-provision/Yealink Device Management Platform
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Reset to factory, reboot
- Package tracing export, system log



Other physical features

- Color: Black
- External Yealink PoE adapter (Optional)
- Power consumption (PoE): 7.3W-20W
- Dimension (W*D*H): 328mm*322mm*62mm
- Operating humidity: 10~90%
- Operating temperature: -10 to +45°C (+14 to 113°F)
- Storage temperature: -30 to +70°C (-22 to +158°F)

Package Features

- Package content:
 - Yealink CP965 IP conference phone
 - Ethernet Cable (7.5m CAT5E UTP cable)
 - M2x5 screw
 - Screwdriver
 - Wireless Microphone CPW65 (Optional)
 - Quick Start Guide
 - Yealink PoE Adapter YLPOE30 (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 7.964 kg
- G.W/CTN: 9.02 kg
- Giftbox size: 398mm*384mm*105mm
- Carton Meas: 552mm*392mm*410mm

Compliance



About Yealink

Yealink (Stock Code: 300628) is a global-leading provider of Unified Communication & Collaboration Solutions specialized in video conferencing, voice communications, and collaboration, dedicated to helping every person and organization embrace the power of "Easy Collaboration, High Productivity".

With best-in-class quality, innovative technology, and user-friendly experiences, Yealink is one of the best providers in more than 140 countries and regions, ranks No.1 in the global market share of IP Phone, and is the Top 5 leader in the video conferencing market (Frost & Sullivan, 2021).

For more information about Yealink, [click here](#).

Copyright

Copyright © 2022 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

Technical Support

Visit Yealink WIKI (<http://support.yealink.com/>) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (<https://ticket.yealink.com>) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Web: www.yealink.com
Addr: No.1 Ling-Xia North Road, High Tech Park,
Huli District, Xiamen, Fujian, P.R.C
Copyright©2022 Yealink Inc. All rights reserved.